



# MATERIAL SAFETY DATA SHEET

## SeaFin Super Spar<sup>®</sup>

Product Number(s): 15200 Series  
 Manufacturer: Daly's Wood Finishing Products  
 3525 Stone Way North  
 Seattle, WA 98103

HMIS Information  
 Health 1  
 Flammability 2  
 Reactivity 0

Emergency Telephone Number:  
 Chemtel (24 Hour): 800-255-3924

Preparer's Name: H. Paulson  
 Date Prepared: 10/10/00  
 Date Reviewed: 08/07/03

### SECTION I - PRODUCT IDENTITY

**Chemical Name:** Resin/Petroleum Solvent Mixture **Chemical Formula:** N/A Product is a mixture.  
**Shipping Classification:** Flammable Liquid, UN 1263, Class 3, PGIII

### SECTION II - HAZARDOUS INGREDIENTS

Chemical & Common Name:	CAS Number:	Wt. %:	OSHA PEL:	ACGIH TLV:	OTHER:
Mineral Spirits	64742-47-8	51	100ppm	500ppm	
Alkylbenzenes	68515-25-3	1	N/A	N/A	
Xylene*	1330-20-7	1	100ppm	100ppm	

\*Denotes a reportable toxic chemical under EPA SARA Title III, Section 313 (40 CFR 372).

### SECTION III - PHYSICAL CHARACTERISTICS

**Boiling Range:** 300-405°F **% Volatile by Volume:** 56%  
**Specific Gravity:** 0.89 **Evaporation Rate(BuOAc=1):** 0.13  
**Vapor Pressure (mm Hg):** 5mm Hg@77°F **Maximum Volatile**  
**Vapor Density (Air=1):** 4.9 **Organic Compound (V.O.C.):** 450 gr/L  
**Solubility (specific solvents):**  
 Soluble in petroleum solvents; insoluble in water.  
**Appearance & Odor:**  
 Dark amber liquid; petroleum distillate odor.

### SECTION IV - FIRE & EXPLOSION DATA

**Flash Point (Setaflash):** 101°F **Flammable Limits (% in Air):** LEL:1.0, UEL: 6.0  
**Extinguishing Media:** CO2, dry chemical, foam, water fog.  
**Special Firefighting Procedures:** Fight as a volatile fire, do not enter enclosed or confined fire spaces without proper protective equipment. This may include self-contained breathing apparatus.  
**Unusual Fire & Explosion Hazards:** None known.  
**Reactivity:** Product is stable. **Hazardous Polymerization:** Will not occur.  
**Conditions to Avoid:** None known.  
**Incompatibilities (materials to avoid):**  
**Hazardous Decomposition Products:** Usual products of combustion CO, CO2, possibly acrolein, and oxides of nitrogen.

### SECTION V - HEALTH HAZARDS

**Primary Routes of Entry:** Eye contact, inhalation, ingestion, skin contact.  
**ACUTE HEALTH EFFECTS:**  
**EYE CONTACT:** May cause redness, irritation.  
**INHALATION:** May cause dizziness, headache, nausea, possible nervous system depression.  
**INGESTION:** May cause nausea, gastrointestinal irritation, or vomiting.  
**SKIN CONTACT:** May cause rash, cracking, dryness or defatting of skin.  
**EMERGENCY FIRST AID PROCEDURES:**  
**EYE CONTACT:** Wash with clean water for at least fifteen minutes; get medical attention.  
**INHALATION:** Move individual to fresh air. If breathing has stopped, apply artificial respiration, get medical attention immediately.  
**INGESTION:** DO NOT INDUCE VOMITING. Give water or milk to drink; get medical attention.

SECTION V - HEALTH HAZARDS(cont'd)

**SKIN CONTACT:** Wash area with soap and water.

**CHRONIC HEALTH EFFECTS:** Not listed as a carcinogen by the NTP, IARC, or OSHA. No adverse long term affects are known.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Pre-existing lung or skin conditions could be aggravated by repeated exposure.

SECTION VI - SPILL OR LEAK PROCEDURES

**Steps to be taken in case material is spilled or released:** Remove all sources of ignition and provide ventilation. Provide respiratory protection required.

**Waste disposal method:** Rags and absorbent material should be immersed in water. Dispose of in accordance with all federal, state and local regulations.

SECTION VII - SPECIAL PROTECTION DATA

**Respiratory protection:** Wear NIOSH-approved respirator for organic vapors. Ensure workers are trained in their proper use.

**Ventilation:** Adequate to keep exposure below TLV.

**Protective Gloves:** Neoprene or rubber.

**Eye Protection:** Goggles.

**Other protective clothing or equipment:** Eyewash station should be available; impervious protective clothing.

SECTION VIII - HANDLING & STORAGE DATA

**Precautions to be taken in handling and storage:** Store away from high temperature, sparks, or open flame. Read and observe all precautions on product label.

**Other precautions:** Store in original container; keep tightly closed. Do not reuse container for other purposes. KEEP OUT OF REACH OF CHILDREN.

SECTION IX - OTHER INFORMATION

Daly's, Inc. certifies that this MSDS meets the requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and EPA SARA Title III Section 313 Supplier Notification (40 CFR 372):

C.A.S. Number  
1330-20-7

Chemical or Common Name  
Xylene

% by Weight  
1

The information contained herein is based on data considered to be accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained for the use thereof. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable regarding all current regulations.

**Daly's Wood Finishing Products**

3525 Stone Way N, Seattle, WA 98103

phone(206) 633-4200

toll free(800) 735-7019

fax(206)632-2565