



Wood Finishing Products

Daly's Waterborne Wood Stain

All Colors

Product:

6/17/2009

SPECIFICATION SHEET

DESCRIPTION: Daly's Waterborne Wood Stain is a penetrating, fade resisting, pigmented stain, containing no measurable environmentally harmful organic solvents.

RECOMMENDED USES: Use on all interior wood surfaces such as furniture, paneling, cabinets, doors and trim. It is not recommended for floors.

RECOMMENDED SYSTEMS: Stir well before and while using. Surface should be dry, clean and smooth. 1. Sand with wood grain with 120 grit sandpaper, finishing with 220 grit, remove sanding dust. DO NOT USE STEEL WOOL. 2. Apply Daly's Waterborne Wood Stain with a synthetic bristle brush, foam brush, rag or staining pad. Wipe with wood grain to desired tone in 1-3 minutes using a rag damp with stain.

FINAL FINISH: Let stain dry minimum of 3-6 hours prior to applying one of Daly's finishes, following the instructions for application.

NOTE 1: To avoid grain raise and spottiness on soft woods, such as pine, fir and hemlock, apply Daly's Benite Wood Conditioner prior to staining.

NOTE 2: Do not stop in middle of surface area when applying. Stain to edge. If a lap should appear, rewet with stain and wipe to uniform color.

NOTE 3: Apply two thin coats rather than one heavy coat. Let dry 2 hours between coats.

NOTE 4: Color may vary due to wood. Test on hidden area prior to application.

NOTE 5: Use Daly's Paste Wood Filler prior to staining, if filling is required.

COLORS & TINTING: Comes in Daly's standard colors that can be intermixed for additional colors. If tinting is required, up to 4 ounces per gallon of universal colorants may be added. Always test for compatibility.

THINNING: Do not thin.

CLEAN UP: Soap and water.

SURFACE PREPARATION: All surfaces to be finished must be free of loose dirt, dust, other contaminants, and must be dry.

APPLICATION: Synthetic bristle brush, foam brush, rag or staining pad.

COVERAGE: Approximately 400 to 500 square feet per gallon.

DRY TIME: 3-6 hours. Temperature, humidity and ventilation will effect dry time.

CAUTIONS: **USE WITH ADEQUATE VENTILATION.** Do not take internally. Close container after each use. If spraying, use an approved NIOSH/MSHA respirator.

First Aid: If swallowed, do not induce vomiting. Call physician immediately. In case of eye contact, flush immediately with plenty of water and get medical attention; for skin, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN.

PROTECT FROM FREEZING.

SPECIAL INSTRUCTIONS: IF SPILLED: Contain spilled materials and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

WARNING: If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC, EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure.

Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

VEHICLE TYPE: Alkyd Emulsion / Acrylic Resin Mixture

WEIGHT PER GAL: 8.6 - 9.3 pounds per gallon

% SOLIDS: 16 to 20% by volume
18 to 23% by weight

FLASH: Product is non-flammable

V.O.C.: < 50 grams per liter.

VISCOSITY: 35 to 45 seconds #2 Zahn Cup

Daly's Wood Finishing Products

3525 Stone Way N, Seattle, WA 98103

phone(206) 633-4200

toll free(800) 735-7019

fax(206)632-2565

S-DWS.pm6-p2/2