



Wood Finishing Products

Benite™ WOOD CONDITIONER

Product:11000

08/05/03

SPECIFICATION SHEET

DESCRIPTION: Daly's **Benite** is a deeply penetrating wood conditioner, which becomes an integral part of the wood structure, there by hardening the wood. **Benite** does not leave a surface film, and reduces the possibility of grain raising. **Benite** is practically odorless and colorless, and because it penetrates, it won't crack, chalk, blister or peel.

RECOMMENDED USES: **Benite** can be used as a wood conditioner, however, for exterior siding applications it is recommended to use a lightly pigmented stain such as Daly's EXTERIOR SEMI- TRANSPARENT STAIN. It is an excellent pre- conditioner to avoid "spotty" stained surfaces, and prevents wood from taking on moisture until stain or finish can be applied. For greater protection on exterior surfaces such as doors and furniture, use Daly's SEAFIN TEAK OIL, SEAFIN SUPER SPAR VARNISH or AQUASPAR.

INTERIOR - Sand wood with 120 grit sandpaper, remove dust, apply with roller, brush, spray or dip. Allow to dry. Sand with 150 or 220 grit sandpaper before staining or finishing over Benite.

EXTERIOR - Apply a full flooding coat. Do not stack treated wood until dry.

THINNING: Not recommends. Product is ready to use packaged.

CLEAN UP: Paint Thinner (Mineral Spirit)

SURFACE PREPARATION: Surface should be free of dust and moisture.

APPLICATION: Brush, roller, spray or most any paint applicator.

COVERAGE: 150 to 200 square feet per gallon on rough surfaces, and 400 to 500 square feet per gallon over smooth wood surfaces.

DRY TIME: Allow 12-24 hours dry time . Temperature and humidity can affect dry time.

CAUTIONS: **CONTAINS PETROLEUM DISTILLATE:** VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

PRECAUTIONS: Keep away from heat and flame. Prevent build-up of vapors by opening windows and doors to achieve cross ventilation.
USE ONLY WITH ADEQUATE VENTILATION.

CAUTIONS (continued): USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Close container after each use.

First Aid: If swallowed, do not induce vomiting. Call physician immediately. If you experience difficulty breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

If spilled: Contain spilled materials and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

VEHICLE TYPE: Alkyd - fortified, Natural oils

WEIGHT PER GAL: 7.0 pounds per gallon.

% SOLIDS: 30% by volume

FLASH: 107°F

V.O.C.: Maximum 550 grams per liter.

Daly's Wood Finishing Products

3525 Stone Way N, Seattle, WA 98103

phone(206) 633-4200

toll free(800) 735-7019

fax(206)632-2565